

## LED 27

### Safety light & escape route light



- Suitable applications for example technical rooms, hallways, control rooms, offices, social spaces
- Housing and diffuser in polycarbonate
- Opalized diffuser
- Available in different versions:
  - Standard central battery system 10-40V DC
  - Standard central battery system 230V AC/DC
  - Addressed central battery system CPS100
  - Addressed central battery system by Teknoware
  - Self-contained - individual 1h/3h battery with automatic self-test function
- Light source LED 4W
- Mounting straight to ceiling or wall, mounting holes at the bottom of the housing (distance 240mm)
- Escape light observation distance 20m
- Connection -0- 5x2,5mm<sup>2</sup> 2xM20 cable glands
- Electrical class I (230V) / III (24V)
- Protection rating IP65



### Product codes

Code	Total power	Voltage	Version	Addressed	Ta	Kg
<b>Safety light</b>						
LED A 27 T1	7 W	10-40V DC	Central battery	No	-30...+35°C	1,1
LED T 27 T1	7 W	230V AC/DC	Central battery	No	-30...+35°C	1,1
LED T 27 T5	8 W	230V AC	CPS100 Central battery	Yes	-30...+35°C	1,2
LED T 27 T7	8 W	230V AC	Teknoware Central battery	Yes	-25...+35°C	1,2
LED B 27 T1	5 W	230V AC	Individual battery 1h/3h	No	5...+35°C	1,5
<b>Escape route light</b>						
LED A 27 x1	5W	10-40V DC	Central battery	No	-30...+35°C	1,1
LED T 27 x1	4W	230V AC/DC	Central battery	No	-30...+35°C	1,1
LED T 27 x5	6W	230V AC	CPS100 Central battery	Yes	-30...+35°C	1,2
LED T 27 x7	6W	230V AC	Teknoware Central battery	Yes	-25...+35°C	1,2
LED B 27 x1	5W	230V AC	Individual 1/3h battery	No	5...+35°C	1,5

### Exit sign arrow directions

Replace x in the product code with referred arrow direction as follows:

X=	A	B	C	D	E	F	H	I
Arrow direction	Down	Right	Left	Up	Stairs down	Stairs up	Stairs down right	Stairs down left